APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

(May 1963)	רואט	TED STATES	(Other instr	uctions on	Budget F	pproved. Bureau No. 42-R1425.
		OF THE INTER	RIOR		5. LEASE DESIGNA	TION AND SERIAL NO.
	GEOLO	GICAL SURVEY			U-7303	AND SERIAL NO.
APPLICATION	N FOR PERMIT	O DRILL, DEEP	EN OR PLUG	RACK	6. IF INDIAN, ALL	OTTER OR TRIBE NAME
1a. TYPE OF WORK	-		<u> </u>	Dr (CIC		*.
DRI b. Type of well		DEEPEN 🗌	PLUG BA	CK 🗌	7. UNIT AGREEME	NT NAME
oir 🖺 G	AS		INGLE MULT	IPLE	S. FARM OR LEAS	PNAME
2. NAME OF OPERATOR	TELL OTHER	Z	ONE ZONE		Gebauer	
Wesgra	Corporation		0)568	MAG	9. WELL NO.	. 4G1 OOM
				H CI	63	
P.O. Box	310-367, Mex	ican Hat, Uta	h 84531.	The state of the s	10. FIELD AND PO	
			state requirentents.)	_1592 	<u>Mexican</u>	
	from the nor	th line	NENT	_	11. SEC., T., R., M. AND SURVEY (, OR BLK. Dr Area
At proposed prod. zon	e oso iron	n th e east li		OF:	Sec 7, 4	2S,19#
14. DISTANCE IN MILES	AND DIRECTION FROM NEAR	REST TOWN OR POST OFFICE	OIL GAS & N	IINING-	12. COUNTY OR PA	BISH 13. STATE
one half 15. DISTANCE FROM PROPO	mile				San Juar	ı Utah
LOCATION TO NEAREST PROPERTY OR LEASE L	2 .	16. NO	O. OF ACRES IN LEASE		F ACRES ASSIGNED	
(Also to nearest drig	t. unit line, if any)		220	3		
TO NEAREST WELL, DI OR APPLIED FOR, ON THI	RILLING, COMPLETED.	N. T.	OPOSED DEPTH	20. ROTAE	Y OR CABLE TOOLS	
21. ELEVATIONS (Show whe	•	74	o' GDRSO	<u>. I</u>	rotary DAT	E WORK WILL START*
4140	22	• 4			1	
23.		ROPOSED CASING AND	CEMENTING PROGR	· AM	ı wnen a	poroved
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT		1		
ייון	10"		SETTING DEPTH	- <u>-</u>	QUANTITY OF C	EMENT
7.7/8"	5美11	28pd 15pd	30' 265'		sacks O sacks	
			20)		U Sacks	
	.			1		
1,2,4,5,9						
3 gunfage	Programa de de la composição	, · · · ·				
5. Surface 1	fromationS	t fromation.	· · · · · · · · · · · · · · · · · · ·	00.		
7. estimated	d depth of wa	ter, oil, or	Goodriage 1	.90' Sodrisa	a 1001	
ro. pressure	equipment	10.000 pd h	low out priv	rentor	, c 190	
II. circulati	ing medium, a	ir & foam	T			
1∠. testing.	logging s	amples only				
ly. approximat	pressures or	temperature	s, none expe	cted -	no hydrog	en sulfate
reasor	ted starting	fter approval				
	arbic oime a	ruer approva.	Merina Even offere			
one. If proposal is to o	iriit or deepen directional	roposal is to deepen or pl ly, give pertinent data or	lug back, give data on p n subsurface locations a	resent produ nd measured	ctive zone and pro and true vertical d	posed new productive lepths. Give blowout
24.			<u> </u>			
200	E Sken					
		TITLE	President		DATE	- 22 - 92
	al or State office use)					O 6
DEREST VO 4.3	· 037-316	100	AF	PROVE	DBYTHE	SIAIE

Company	Wesgro Oil Corp.		
Well Name & No	Gebauer-Groom No. 63		
Location	835' F/NL 680' F/EL		
Sec, T S.,	R E., S. L. M., County	San Juan	, Utgh
Ground Elevation 414			
			1
3			

		835' — 680'—
Section	7	

Scale, 1 inch = 1,000 feet

Surveyed	October 16	10	91
		. 17	

This is to certify that the above plat was prepared from field notes of actual surveys made by me or under my supervision and that the same are true and correct to the best of my knowledge and belief.

Seal:




Edgar L. Risenhoover Registered Land Surveyor New Mexico Reg. No. 5979

Non-resident certification as authorized by Utah State Law

58-22-21(b)

	8 ,
PERATOR plesgio Corporation N-10100. DATE 90:10.90	·
ELL NAME Wilderi- Groom #63.	
EC NENE 7 T 425 R 19F COUNTY Van Than	•
	•
43-037-31660 Federal (1) API NUMBER TYPE OF LEASE	
CHECK OFF:	
PLAT. BOND NEAREST WELL	
LEASE . FIELD POTASH OR OIL SHALE	
PROCESSING COMMENTS: Linustucted spacing falls: within Cause quid	ılır
water Permit	
Wall Flims	
	•
\$55.C	
APPROVAL LETTER:	•
SPACING: R615-2-3 NA RS15-3-2	•
150-3 J-15-80 R615-3-3 CAUSE NO. & DATE	•
STIPULATIONS:	
SIT-OCATIONS.	
1- Merold water primit	•
	-
	_
	-





355 West North Temple 3 Triad Center, Suite 350 Salt Lake City, Utah 84180-1203 801-538-5340

February 7, 1992

Wesgra Corporation P. O. Box 310-367 Mexican Hat, Utah 84531

Gentlemen:

Re: Gebauer-Groom #63 Well, 835 feet from the north line, 680 feet from the east line, NE 1/4 NE 1/4, Section 7, Township 42 South, Range 19 East, San Juan County, Utah

Pursuant to Utah Code Ann. § 40-6-6, (1953, as amended) and the order issued by the Board of Oil, Gas and Mining in Cause No. 156-3 dated April 15, 1980, approval to drill the referenced well is hereby granted.

In addition, the following specific actions are necessary to fully comply with this approval:

- Submittal to the Division of evidence providing assurance of an adequate and approved supply of water as required by Utah Code Ann. § 73-3, Appropriations, prior to commencing drilling operations.
- 2. Compliance with the requirements of Utah Admin. R. 649-1 et seq. (formerly 615-1 et seq.), Oil and Gas Conservation General Rules.
- 3. Notification within 24 hours after drilling operations commence.
- 4. Submittal of Entity Action Form, Form 6, within five working days following commencement of drilling operations and whenever a change in operations or interests necessitates an entity status change.
- 5. Submittal of the Report of Water Encountered During Drilling, Form 7.

Page 2 Wesgra Corporation Gebauer-Groom #63 February 7, 1992

- 6. Prompt notification prior to commencing operations, if necessary, to plug and abandon the well. Notify Frank R. Matthews, Petroleum Engineer, (Office) (801)538-5340, (Home) (801)476-8613, or R.J. Firth, Associate Director, (Home) (801)571-6068.
- 7. Compliance with the requirements of Utah Admin. R. 649-3-20 (formerly 615-3-20), Gas Flaring or Venting, if the well is completed for production.

Prior to commencement of the proposed drilling operations, plans for facilities for disposal of sanitary wastes at the drill site should be submitted to the local health department. These drilling operations and any subsequent well operations should be conducted in accordance with applicable state and local health department regulations. A list of local health departments and copies of applicable regulations are available from the Department of Environmental Quality, Division of Drinking Water/Sanitation, telephone (801)538-6159.

This approval shall expire one (1) year after date of issuance unless substantial and continuous operation is underway or an application for an extension is made prior to the approval expiration date. The API number assigned to this well is 43-037-31660.

Sincerely,

Associate Director, Oil and Gas

ots Enclosures

cc: Bureau of Land Management

J.L. Thompson

WOI1



(Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1425.

UNITED STATES

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1a. TYPE OF WORK DRILL DEEPEN DPLUG BACK 7. b. TYPE OF WELL SINGLE SINGLE SONE 8. 2. NAME OF OPERATOR	U-7303 IF INDIAN, ALLOTTEE OR TRIBE NAME UNIT AGREEMENT NAME
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1a. TYPE OF WORK DRILL X DEEPEN D PLUG BACK 7. b. TYPE OF WELL GAS WELL OTHER OIL X OTHER SINGLE ZONE SONE 8.	UNIT AGREEMENT NAME
DRILL X DEEPEN D PLUG BACK 7. b. TYPE OF WELL OIL	
OIL GAS WELL OTHER SINGLE ZONE 8. NAME OF OPERATOR	
2. NAME OF OPERATOR	FARM OR LEASE NAME
Wesgra Corporation 3. ADDRESS OF OPERATOR	Gebauer-Groom
3. ADDRESS OF OPERATOR	WELL NO.
<u> </u>	63
r.u. Box 110-107. Mexican Hat. Utan 8/531	FIELD AND POOL, OR WILDCAT
At surface	Mexican Hat
	. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
43-057-37660	Sec 7, 42S, 19解
	COUNTY OR PARISH 13. STATE
OHE HALL MILE	San Juan Utah
LOCATION TO NEAREST TO THIS	CRES ASSIGNED WELL
(Also to nearest drig. unit line, if any)	OR CABLE TOOLS
TO NEAREST WELL, DRILLING, COMPLETED.	
1 1 7	Otary 22. APPROX. DATE WORK WILL START*
4140°	
23. PROPOSED CASING AND CEMENTING PROGRAM	when approved
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH	QUANTITY OF CEMENT
	acks
$7.7/8"$ $5\frac{1}{2}$ " 15pd 265! 20	sacks
DES	1 5 1992
DIVI OIL GA	SION OF S & MINING
	egeneration (not become a second control of the second control of
IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productizone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured an preventer program, if any. 24.	

PERMIT NO. /S/ WILLIAM C. STRINGER

Assistant District Manager TITLE - for Minerals

President

APPROVAL DATE _


APR 1 3 1992 DATE _

CONDITIONS OF APPROVAL, IF ANY :

FLARING OR VENTING OF GAS IS SUBJECT TO NTL 4-A Dated 1/1/80

(This space for Federal or State office use)


*See Instructions On Reverse Side



Surveyed	October 16	10	91
		1.7.	

This is to certify that the above plat was prepared from field notes of actual surveys made by me or under my supervision and that the same are true and correct to the best of my knowledge and belief.

Seal:



Non-resident certification as authorized by Utah State Law 58-22-21(b)

Wesgra Corporation
Gebauer-Groom No. 63
NENE Sec. 7, T. 42 S., R. 19 E.
San Juan County, Utah
Lease U-7303

CONDITIONS OF APPROVAL

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Be advised that Wesgra Corporation is considered to be the operator of the above well and is responsible under the terms and conditions of the lease for the operations conducted on the leased lands.

Bond coverage for this well is provided by UT0251 (Principal - Wesgra Corporation) via surety consent as provided for in 43 CFR 3104.2.

This office will hold the aforementioned operator and bond liable until the provisions of 43 CFR 3106.7-2 continuing responsibility are met.

This permit will be valid for a period of one year from the date of approval. A one-time, 90 day extension of this period may be granted. After permit termination, a new application must be filed for approval.

All lease operations will be conducted in rull compliance with applicable regulations (43 CFR 3100), Onshore Oil and Gas Orders, lease terms, notices to lessees, and the approved plan of operations. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions and the approved plan will be made available to field representatives to insure compliance.

A. DRILLING PROGRAM

- 1. There will be no deviation from the proposed arilling and/or workover program without prior approval from the Assistant District Manager. "Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3162.3-2. Safe drilling and operating practices must be observed.
- 2. No trivalent or hexavalent chromate additives shall be used in the mud system. Due to potential for contamination of usable quality water aquifers, chromates are banned from Federal leases.

- 3. Pressure control equipment shall be used when necessary in accordance with the variance granted Wesgra Corporation via letter dated April 8, 1992, and Onshore Oil and Gas Order No. 2.
- 4. Operations authorized by this permit shall not be suspended for more than 30 days without prior approval of the Authorized Officer. All conditions of this approval shall be applicable during any operations conducted with a replacement rig.
- 5. Should the well become productive, the BLM, District Office must be notified no later than five business days after production begins. Notification shall be by letter or sundry notice, or orally to be followed by a letter or sundry notice.
- 6. Gas produced from this well may not be vented or flared beyond an initial authorized test period of 30 days or 50 Mmcf following its completion, whichever comes first, without prior written approval of the Authorized Officer.

B. Stipulations:

- All site security guidelines identified in 43 CFR 3162.7-5 and ONSHORE OIL AND GAS ORDER NO. 3; SITE SECURITY will be adhered to.
- 2. Gas measurement will be conducted in accordance with the <u>ONSHORE OIL</u> AND GAS <u>ORDER NO. 5; GAS MEASUREMENT</u> and 43 CFR 3162.7-3.
- 3. Oil measurement will be conducted in accordance with <u>ONSHORE OIL AND</u> GAS ORDER NO. 4; OIL MEASUREMENT and 43 CFR 3162.7-2.
- 4. Pad construction material will be obtained from on site and in place materials.
- 5. The reserve pit will be fenced within 24 hours after drilling operations cease with four (4) strands of barbed wire, or woven wire topped with barbed wire to a height of not less than four (4) feet. The fence will be kept in good repair while the pit is drying. OR all liquids can be removed from the pit and the pit can be filled in with the excavated material and seeded.
- 6. NO LIQUID HYDROCARBONS (i.e. fuels, lubricants, formation)WILL BE DISCHARGED TO THE RESERVE PIT, LOCATION, OR ON THE ACCESS ROAD.
- 7. No chrome compounds will be on location.
- All flow lines and electrical lines will be buried.
- 9. All permanent above-ground facilities (in place six months or longer) will be painted a neutral, nonreflective <u>SAND</u> color as required by the Authorized Officer, except for those facilities or portions thereof required to comply with the Occupational Safety and Health Act or written company safety manual or documents. The paint on the surfaces of the facilities will be maintained as required by the Authorized Officer.

- 10. If a tank battery is constructed on this location it will be surrounded by a dike of sufficient capacity to contain 1.5 times the storage capacity of the largest tank + one days production entering the battery. All load lines and valves will be placed inside the dike surrounding the tank battery. The tank battery and berm, any pits, and any production facilities shall be fenced and the fence will be maintained. The gates shall be kept closed.
- 11. Within 24 hours of completion of drilling, the location and surrounding area will be cleared of everything not required for production.
- 12. As soon as the reserve pit has dried all areas not needed for production (including the access road) will be filled in, contoured to approximately natural contours and as much top soil as was removed replaced leaving sufficient for future restoration. The remaining top soil will be stabilized and seeded in place. If the well is a dry hole, the location and access road will be rehabilitated in total.
- 13. The area will be seeded between October 1 and February 28 with:

6 lbs/acre Fourwing saltbush OR6 lbs/acre Shadscale

The pounds of seed listed above is pure live seed.

Seed will be broadcast followed by a light harrowing.

- 14. All wells, whether drilling, producing, suspended, or abandoned and/or separate facilities, will be identified in accordance with 43 CFR 3162.6.
- 15. "Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3162.6.
- 16. The operator is responsible for informing all persons in the area who are associated with this project that they will be subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, the operator is to immediately stop work that might further disturb such materials, and contact the authorized officer (AO). Within five working days the AO will inform the operator as to:
 - whether the materials appear eligible for the National Register of Historic Places;
 - the mitigation measures the operator will likely have to undertake before the site can be used (assuming in-situ preservation in not necessary); and,
 - a timeframe for the AO to complete an expedited review under 36 CFR 800.11 to confirm, through the State Historic Preservation Officer, that the findings of the AO are correct and that mitigation is appropriate.

If the operator wishes, at any time, to relocate activities to avoid the mitigation and/or the delays associated with this process, the AO will assume responsibility for whatever recordation and stabilization of the exposed materials may be required. Otherwise, the operator will be responsible for mitigation costs. The AO will provide technical and procedural guidelines for the conduct of mitigation. Upon verification from the AO that the required mitigation has been completed, the operator will then be allowed to resume construction.

B. SURFACE USE PLAN

u/4 inch thid), an

- 17. The dirt contractor will be provided with an approved copy of the surface use plan of operations before initiating construction.
- 18. The reserve pit shall be located in cut material, with at least 50% of the pit volume being below original ground level. As soon a the reserve pit has dried, all areas not needed for production will be rehabilitated.
- 19. Surface disturbance and vehicular travel will be limited to the approved location and access road. Any additional area needed must be approved by the Area Manager in advance.
- 20. Trash must be contained in a trash cage and hauled away to an approved disposal site as necessary but no later than at the completion of drilling operations.
- 21. All off-lease storage, off-lease measurement, or commingling (on-lease or off-lease) shall have prior written approval from the Assistant District Manager.
- 22. Copies of all water analysis required by the State of Utah in relation to surface discharge of produced water will be submitted to the Moab District Office, Bureau of Land Management.
- 23. Produced waste water will be confined to an unlined pit for a period not to exceed ninety (90) days after initial production. During the ninety (90) day period, an application for approval of a permanent disposal method and location, along with the required water analysis, will be submitted for the Assistant District Manager's approval pursuant to NTL-2B.
- 24. If at any time the facilities located on public land authorized by the terms of the lease are no longer included in the lease (due to contraction in the unit or other lease or unit boundary change) the BLM will process a change in authorization to the appropriate statute. The authorization will be subject to appropriate rental, or other financial obligation determined by the authorized officer (AO).

25. When the well is abandoned, all casing shall be cut-off at the cellar or three feet below restored ground level. The abandonment marker must be either, 1) a four inch pipe, at least ten feet in length embedded in cement with four feet remaining above ground, or 2) a metal plate at least 1/4 inch thick and welded in place. A weep hole shall be left in the metal plate. In either case, the marker must be inscribed with the following: operator name, lease number, well name and surveyed description (township, range, section and either quarter-quarter or footages).

and either quarter-quarter or footages).

These requirements shall be in effect unless specifically waived in writing by the authorized officer.

C. REQUIRED NOTIFICATIONS AND APPROVALS

Required verbal notifications are summarized in Table 1, attached.

Spud-Written notification in the form of a Sundry Notice (Form 3160-5) will be submitted to the District office within twenty-four (24) hours after spudding (regardless of whether spud was made with a dry hole digger or big rig). If the spudding occurs on a weekend or holiday, the written report will be submitted on the following work day.

Undesirable Events/Immediate Reports- Spills, blowouts, fires, leaks, accidents, or any other unusual occurrences shall be immediately reported to the Resource Area in accordance with requirements of NTL-3A.

<u>Cultural Resources</u>— If cultural resources are discovered during construction, work that might disturb the resources is to stop, and the Area Manager is to be notified.

First Production- Should the well be successfully completed for production, the Assistant District Manager, Minerals Division will be notified when the well is placed in producing status. Such notification may be made by phone, but must be followed by a sundry notice or letter not later than five (5) business days following the date on which the well is placed on production.

A first production conference will be scheduled within fifteen (15) days after receipt of the first production report. The Resource Area Office will coordinate the field conference.

Well Completion Report—Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (Form 3160-4) will be submitted to the District Office not later than thirty (30) days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs, core descriptions, core analyses, well test data, geologic summaries, sample description, and all other surveys or data obtained and complied during the drilling, workover, and/or completion operations, will be filed with Form 3160-4. Samples (cuttings, finids, and /or gas) will be submitted when requested by the Assistant District Manager.

Plugging and Abandonment- If the well is completed as a dry hole, plugging instructions must be obtained from the BLM. Most District Office prior to initiating plugging operations. Table 1 of this document provides the after-hours phone numbers of personnel who are authorized to give plugging instructions.

A "Subsequent Report of Abandonment" (Form 3160-5) will be filed with the Assistant District Manager, Minerals Division within thirty (30) days following completion of the well for abandonment. This report will indicate where plugs were placed and the current status of surface restoration. Upon completion of approved plugging, a regulation marker will be erected in accordance with 43 CFR 3162.6. Final abandonment will not be approved until the surface reclamation work required by the approved APD or approved abandonment notice has been completed to the satisfaction of the Area Manager or his representative, or the appropriate surface managing agency.

Venting/Flaring of Gas-NTL-4A allows venting/flaring of gas during the initial well evaluation period not to exceed 50 days or 50 Mmcf. Venting/flaring beyond the initial test period threshold must be approved by the District Orfice.

NOTIFICATIONS

Notify Bob Turri or Jeff Brown of the San Juan Resource Area, at (801) 587-2141 for the following:

2 days prior to commencement of dirt work, construction or reclamation:

l day prior to spudding;

If the person at the above number cannot be reached, notify fred Oneyear in the Moab District Office at (801) 259-6111 or at home at (801) 259-5937. If unsuccessful, notify one of the people listed below.

Well abandonment operations require 24 noor advance notice and prior approval. In the case of newly drilled dry hores, verbal approval can be obtained by carling the moan practice Office, Branch of Fluid Minerals at (801) 259-5111. If approval is deeded after work hours, you may contact the forcewing:

Dale Manchester, Petroleum Engineer Orfice: (801) 259-6:11

Eric Jones, Petroleum Engineer Office: (601) 259-6111 nome: (601) 259-2214

If unable to reach the above individuals, please wall one following:

Lynn Jackson.

Onfice: (a01) 209-6111
Chief, Branch of Fluid Minerals

Home: (801) 259-7990

Form 3160-3 (November 1983) (formerly 9-331C)

SUBMIT IN TRIPLICATE.

(Other instructions on reverse side)

Form approved. Budget Bureau No. 1004-0136 Expires August 31, 1985


UNITED STATES DEPARTMENT OF THE INTERIOR

	BUREAU OF	LAND MANAGEME	NT		U-7303
	N FOR PERMIT	O DRILL, DEEF	PEN, OR PLUG E	BACK	6. IF INDIAN, ALLOTTER OR TRIBE NAME
TYPE OF WORK TYPE OF WELL		DEEPEN	PLUG BA	CK 🗆	7. UNIT AGREEMENT NAME
VELL X	VELL OTHER		SINGLE MULTIF	PLE	8. FARM OR LEASE NAME
AME OF OPERATOR		· · · · · · · · · · · · · · · · · · ·			Gebauer-Groom
# Wesgra	Corporation				9. WELL NO.
DDRESS OF OPERATOR					63
P.O. Box	310-367, Mexi	can Hat, Uta	th 84531		10. FIELD AND POOL, OR WILDCAT
t surface		the north lir			Mexican Hat
	6801 from	the east li			11. BEC., T., R., M., OR BLK. AND SURVEY OR AREA
t proposed prod. zo	ne OOO II On	i one cast in	.116		1 N.c. N.c. Sec 7 425,
DISTANCE IN MILES	AND DIRECTION FROM NEA	REST TOWN OR POST OFFI	CB*		12. COUNTY OR PARISH 13. STATE
	lf mile				Con Inch
DISTANCE FROM PROP LOCATION TO NEARES	USED*	16.	NO. OF ACRES IN LEASE		San Juan Utah
PROPERTY OR LEASE (Also to nearest dri	LINE DA 2	001	250	TO T	HIS WELL 5
DISTANCE FROM PRO	POSED LOCATION	19.	PROPOSED DEPTH	20. ROTA	BY OR CABLE TOOLS
OR APPLIED FOR, ON TH	POSED LOCATION* DRILLING, COMPLETED, HIS LEASE, FT.	3001	7501		rotary
ELEVATIONS (Show wh	nether DF, RT, GR, etc.)	The state of the s			22. APPROX. DATE WORK WILL START*
41	401		<u>.</u>		when approved
	Argani ya katawa ka J	PROPOSED CASING AN	ND CEMENTING PROGR	AM	
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	1	QUANTITY OF CEMENT
		.			
131"	10"	24.00	301		5 sacks
131" 9"	05/8"	24pd 17pd	30' 280'		5 sacks 20 sacks
1,2,4,5, 3. surfa 6. estim 7. estim 10. press 11. crecu 12. testi 19. abnor 14. antic there	8,9 ce formation lated iop of wated top of grand medium medium mal pressures ipated startiafter. dura proposed PROGRAM: If drill or deepen directions	Suparater, water, geological mair oles only or temperating time, when the depth lite proposal is to deepen or	280' oil or gas rker Go not required and foam ures, none n approved or	no H	Goodridge 230' ge 230' ydrogen sulfite onable time
1,2,4,5, 3. surfa 6. estim 7. estim 10. press 11. circu 12. testi 10. abnor 14. antic there	8,9 ce formation lated iop of wated top of grand medium medium mal pressures ipated startiafter. dura proposed PROGRAM: If drill or deepen directions	Suparater, water, geological mair oles only or temperating time, when the depth lite proposal is to deepen or	280' oil or gas rker Go not required and foam ures, none n approved or	no H	Goodridge 230' ge 230' ydrogen sulfite onable time 9 days 000 750'
1,2,4,5, 3. surfa 6. sstim 7. estim 10. press 11. circu 12. testi 16. abnor 14. antic there	8,9 ce formation lated iop of wated top of grand medium medium mal pressures ipated startiafter. dura proposed PROGRAM: If drill or deepen directions	Suparater, water, geological mair oles only or temperating time, when the depth lite proposal is to deepen or	oil or gas orker Go and foam oures, none on approved or ling the loop zone on subsurface locations a	no H	Goodridge 230' ge 230' ydrogen sulfite onable time 9 days 000 750' ductive some and proposed new productive id and true vertical depths. Give blowout
1,2,4,5, 3. surfa 6. estim 7. estim 10. press 11. crecu 12. testi 10. abnor 14. antic there	ce formation lated iop of wated top of gure equipment lating medium ng samp mal pressures ipated starting after. dura proposed program: If drill or deepen direction ny.	Suparater, water, geological mair oles only or temperating time, when the depth lite proposal is to deepen or	oil or gas orker Go and foam oures, none on approved or ling the loop zone on subsurface locations a	no H	Goodridge 230' ge 230' ydrogen sulfite onable time 9 days 000 750' ductive some and proposed new productive d and true vertical depths. Give blowout
1,2,4,5, 3. surfa 6. sstim 7. estim 10. press 11. crecu 12. testi 19. abnor 14. antic there BOVE SPACE DESCRIB H proposal is to enter program, if an	ce formation lated iop of wated top of gure equipment lating medium ng samp mal pressures ipated starting after. dura proposed program: If drill or deepen direction ny.	Suparater, water, geological mair oles only or temperating time, when the depth lite proposal is to deepen or	oil or gas orker Go and foam oures, none on approved or ling the loop zone on subsurface locations a	no H	Goodridge 230' ge 230' ydrogen sulfite onable time 9 days 000 750' ductive some and proposed new productive d and true vertical depths. Give blowout
1,2,4,5, 3. surfa 6. sstim 7. estim 10. press 11. crecu 12. testi 16. abnor 14. antic there	ce formation lated iop of wated top of gure equipment lating medium ng samp mal pressures ipated starting after. dura proposed program: If drill or deepen direction ny.	Suparater, water, geological mair oles only or temperating time, when the depth lite proposal is to deepen or	oil or gas orker Go not required and foam cures, none en approved or ling tle loop zone plug back, give data on p on subsurface locations a	no H	Goodridge 230' ge 230' ydrogen sulfite onable time 9 days 000 750' ductive some and proposed new productive id and true vertical depths. Give blowout

*See Instructions On Reverse Side

DIVISION OF OIL GAS & MINIMY

Company	Wesgro Oil Corp.	BECENYE
Well Name & No	Gebauer-Groom No. 63	SEP 0 2 1992
Location	835' F/NL 680' F/EL	DIVISION OF OIL GAS & MINING
Sec 7 , T 42 S., Ground Elevation _ 4140	R. 19 E., S. L. M., County San Juan	



Scale, 1 inch = 1,000 feet

~	•				
Surveyed	Uctober	16			_
	40.00001	10	10	Q 1	1
	.,		 		

This is to certify that the above plat was prepared from field notes of actual surveys made by me or under my supervision and that the same are true and correct to the best of my knowledge and belief.

Seal:



Edgar L. Risenhoover
Registered Land Surveyor
New Mexico Reg. No. 5979

Non-resident certification as authorized by Utah State Law 58-22-21(b)

DIVISION OF OIL, GAS AND MINING

SPUDDING INFORMATION

NAME OF COMPANY: WESGRA		43-037-	31660
WELL NAME: GREBAUER	GROOM	# 63	
Section 7 Township	425	Range 19E	County <u>SAN JUAN</u>
Drilling Contractor	QUALITY	DRILLING	
Rig #1			
SPUDDED: Date 9/17/92	····		
Time			
How_ROTARY			
Drilling will commence			**************************************
Reported by BILL SKEEN			
Telephone #			
Data 9/17/92	STC:	NED	FRM

DIVISION OF DIL, GAS AND MINING ENTITY ACTION FORM - FORM 6 Wesgra Corporation

OPERATOR ACCT. NO. H N-1060

ADDRESS

P.O. Box 310-367

Mexican Hat, Utah 84531

WELL NAME WELL LOCATION CURRENT ! NEW API NUMBER ACTION SPUD EFFECTIVE ENTITY NO. ENTITY NO. SC RG COUNTY DATE CODE DATE B 4303731660 Gebauer-Groom #63 NENE 423 9-18-92 19E 11004 . 11004 San Juan Entity added 9-29-92. fee WELL 1 COMMENTS: WELL 2 COMMENTS: WELL 3 COMMENTS: WELL 4 COMMENTS: SEP 2 5 1992 **DIVISION OF** O'L GAS & MINING WELL 5 COMMENTS:

ACTION CODES (See instructions on back of form)

A - Establish new entity for new well (single well only)

B - Add new well to existing entity (group or unit well)
C - Re-assign well from one existing entity to another existing entity

D - Re-assign well from one existing entity to a new entity

E - Other (explain in comments section)

NOTE: Use COMMENT section to explain why each Action Code was selected.

(3/89)

Presisdent

Title

Phone No.

Form 3160-5 (May 1989)

REPAIR WELL

(Other)

D STATES

SUBMIT IN TRIPL
(Other instructions

SHOOTING OR ACIDIZING

FORM APPROVED OMB NO. 1004-0135 Expires: September 30, 1990

ABANDONMENT

BUREAU OF LAND MANAGEMENT	U-7303		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
OIL GAS OTHER	7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR Wesgra Corporation	8. FARM OR LEASE NAME Gebauer-Groom		
P.O. Box 310-367, Mexican Hat, Utah 84531	9. WELL NO. 63		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 835! from the north line	10. FIELD AND POOL, OR WILDCAT Mexican Hat		
680' from the east line	11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA Sec 7, 42S, 19E		
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 43-037-31660 4140!	12. COUNTY OR PARISH 13. STATE San Juan Utah		
16. Check Appropriate Box To Indicate Nature of Notice, Report, or O	Other Data		
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE ARANDON®	REPAIRING WELL ALTERING CASING		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and gones pertinent to this work.) •

Plugged 9-30-92

CHANGE PLANS

50' of cement across the zone

50' across the shoe on bottome of casing

30' in top of pipe

DIVISION OF OIL GAS & MINING

8. I hereby certify that the foregoing is true and correct SIGNED	TITLE	President		DATE	10-5-92
(This space for Federal or State office use)				(45)	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		· · · · · · · · · · · · · · · · · · ·	DATE _	

*See Instructions on Reverse Side



801-538-5340

January 28, 1993

Wesgra Corporation P.O. Box 310-367 Mexican Hat. Utah 84531

Gentlemen:

Division Director

Well Completion Report - Gebauer-Groom 63 Well, Sec. 7, T. 42S, R. 19E, San Re: Juan County, Utah, API No. 43-037-31660

Utah Admin, R649-3-21, the Utah Oil and Gas Conservation General Rules, requires that within 30 days after the completion of any well drilled or redrilled for the production of oil or gas, Well Completion or Recompletion Report and Log, Form 8, and copies of the electric and radioactivity logs, if run, shall be filed with the division. Utah Admin. R649-8-9 adds that Form 8 and accompanying logs shall be submitted within 30 days after recompleting a well or plugging a newly drilled well.

Our records indicate that the Well Completion Report for the referenced well has not been received. Enclosed is a copy of Form 8 for your use in promptly submitting this report. If you have questions regarding the completion of the form, please feel free to call Debra Eatchel at the above number.

Sincerely,

Don Staley Administrative Manager

Oil and Gas

idc

Enclosure

CC:

R.J. Firth

D.M. Eatchel

Well file

WOI1

Form 3160-5 (June 1990)

TYPE OF SUBMISSION

Final Abandonment Notice

Notice of Intent

Subsequent Report

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM	I APPR	OVED
Budget Bure	eau No.	1004-0135
Expires:	March	31, 1993

5. Lease Designation and Serial No. U-7303

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well X Oil Well 8. Well Name and No. 2. Name of Operator Gebauer-Groom Wesgra Corporation 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area P.O. Box 310-367, Mexican Hat, Utah 34531 ph. 301 633 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Mexican Hat 11. County or Parish, State o30' from the east line 335' from the north line 43-037-31660 Sec 7 San Juan, Whali 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

Well was drilled and proved dry, so it was plugged while rig was supervised by BLM personal

TYPE OF ACTION



Change of Plans New Construction

Non-Routine Fracturing Water Shut-Off

Conversion to Injection Dispose Water

DIVISION OF OIL GAS & MINING

4. I hereby certify that the foregoing is true and correct Signed	TitlePresident	Date <u>2-16993</u>
(This space for Federal or State office use)		
Approved by	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

TED STATES SUIDEPARTMENT OF THE INTERIOR

SUBMIT IN DUF

FOR APPROVED OMB NO. 1004-0137 Expires: December 31, 199

	DEPA	RTME	O TV	FTH	E IN	NTERIC	R		wother in		pires: [December 31, 1991
		BUREAU	OF LAN	NAM DA	AGEM	ENT	•		erse side)	5. I.KASE U-7		NATION AND SERIAL P
WELL (OMPLETIC	N OR	RECO	MPLET	ION	REPORT	AN	ND LC)G *			LOTTER OR TRIBE NAI
la. TYPE OF	WELL:	WRILL A	WELL [J ,	RY 🗍	Other				7 UNIT A		
L TYPE OF C	OMPLETION:							·			CREEN	ENT NAME
well L	OVER	EN DEEL	nvck [DIFF	R	Other				8. FARM	OR I.	FASE NAME WELL
2. NAME OF OP										Ge	bau	ease Name, Well
Wes	gra Corpo	ration	1		Phor	ne 80k	683	-2298	3	9. API WE	LL NO.	
				***			^ •	TO -			63	3
4. LOCATION OF	Box 310-3 WELL (Report loc	667, M€	xica	n Hat	, Ut	an 845	26	רובוי	MS	ID. FIELD	AND P	OOL, OR WILDCAT
At surface	(111)	arion crearing	272 17 0	from	with a	north	3	JUDIT	n fe	Mex	icar	n H at
A4 440 504		68	ijj Kni f	LLOW T	ba a	east li	ne Til			OR AR	Г., R., <u>М</u> Ед	OR BLOCK AND SURVI
at top prog.	interval reported	below O		I Om U	116	304 DO	"FE	B 18	1993	Sec	7,	42 ⁵ , 19E
At total dep	1							-				
				14. PER	MIT NO).	D CH	VISION	1 OF	12. COUNT	YOR	13. STATE
				43-	037-	-31660 d	F	h (00)	MINING	The PARISE	١_	_
5. DATE SPUDDE	1	REACHED	17. DATE	COMBI	Da-d	4 4 1	JIL C	V+TIQNA (DF. RKS.	RT. GR. ETC.)	19.	ELEY. CASINGHEAD
ept 21	Sept				eq-	30-9a	4	140.				
7401	MD A TVD 21.	PLUG. BACK T.	D., MD & 1	rvo 22.	IF MUI	TIPPEPMS	und	¥ 23. IN	TERVALS	ROTARY T	00L8	CABLE TOOLS
	TERVAL (C) OF THE			į.		או אשפח	LR_	7a		rotar	У	
מימ ספר	ducing i	IS COMPLETE	ONTOP,	BOTTOM,	SHAP	MD AND TVD)	•				i	25. WAS DIRECTIONAL SURVEY MADE
no pro	daorne I	acerva.	LS		•						 	SCAVEL MADE
TYPE ELECTRI	C AND OTHER LOG	a at's				· · · · · · · · · · · · · · · · · · ·						
		es only	,								1	WAS WELL CORED
1.	Sampi	OS CAL		C PECOP	D / Par	port all string					1 '	no
CASING SIZE GRAD	E WEIGHT. L	B./FT. DE	PTH SET	(MD)		I.E. SIZE	s set :		FMENT CE	MENTING DECO		
10"	40	pd	301		-1	24"	·		OF CEMENT, CEMENTING REC		-	AMOUNT PULLED
6 5/8"	15	pd	2051			7 7/8"	 	25	sacks sacks			
												
	<u> </u>											
	1 707 (117)	LINER R						30.	1	UBING REC	ORD	
	TOP (MD)	POTTOM	(MD)	SACKS CEN	ENT*	SCREEN (M	D)	SIZE		PEPTH SET (MD)	PACKER SET (MD)
		-	 -									
. PERFORATION I	ECOED (Interval,	size and nur	nber)			1 00						
well blu	gg d whe	fiie	sh-ad			32.				URE. CEMEN		· · · · · · · · · · · · · · · · · · ·
supervis	led by BL	W perso	onal					120,	A 310	JUNT AND KI	ND OF	MATERIAL USED
		· pars.										
TE PIRET PRODUC	TION	011001011				T'CTION					******	
	740	DUCTION MET	HOD (Flo	owing, gas	lift, pu	mping-eize	and ty	pe of pun	(p)		STATU	8 (Producing or
TS OF TEST	HOURS TESTE	CHOK		1 secolu				- 1			•	PA
		1	- 4.23	PROD'N. TEST PE		OILBBL.	1	GAS-MC	rr.	WATER—BB	L.	GAS-OIL BATIO
W. TUNNS PROC	CASING PRESS			011,881	->	GAS	1		WATER	W 0 1		0.0147
			R RATE	1				1	- A . C.	~~ .	UIL G	RAVITY-API (CORE)
. DISPOSITION OF	GAB (Bold, used f	r fuel, vente	d, etc.)							TEST WITHE	BED B	T
•												
. LIST OF ATTAC	ENENTS					····						
I hereby south	T that she s											
	y that the forego	ing and atta	ched info	rmation is	compl	ete and corre	ct as	determine	d from a	il available r	ecords	
SIGNED	18 C 6	Rec	\sim	M-		reside						-16-93
				TITL	Bi.					D 4 783	· ·~	

*(See Instructions and Spaces for Additional Data on Reverse Side)

Form 3160-14 (April 1987)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

INDIVIDUAL WELL RECORD

Sec			
T	42	S.	,
R	19	Ε.	
SLE	3&		Mer

	0

			R19	
	t 27, 1993		SLB&	
FEDERAL	State	Utah		
Lease No7303	County	San Juan		
Lessee Wesgra Corporation 100%	Field	Mexican Hat		
Operator <u>Wesgra Corporation</u>	Unit/CA			
Well Name & No. Gebauer-Groom 63				
A.P.I. Well No. 43-037-31660	Subdivision	NENE		
Location835' FNL & 680' FEL				
Date Drilling Approved April 13, 1992	Well Elevation	4140		Fee
Date Drilling Commenced September 17, 1992				Feet
Date Drilling Ceased October 1, 1992	Initial Production	D 11 7		
Date Completed For Production	Gravity A.P.I.			
SUL APPONITO 11/11/93 Date Abandonment Approved (Final)	Initial Reservoir Pressu	re		

GEOLOGIC FORMATIONS

PRODUCTIVE HORIZONS

surface Supa i	LOWEST TESTED	NAME.	DEPTHS	CONTENTS
SURFACE MANAGEMENT AGENCY	BLM			
MINERAL OWNERSHIP	BLM	_		
LEASE EXPIRATION	2/29/79			

WELL STATUS

YEAR	JAN.	FEB.	MARCH	APRIL	MAY	JUNE	JULY	AUG.	SEPT.	OCT.	NOV.	DEC.
1992									SPUD	Dry Hol	е	<u></u> .
1993						Sub. of Memo to SJRA		2nd Men to SJR/	О		Spa Approved	
						JOIN						
·												_ ,,
					·							
										1		

narks	 	
•		

